

Code: **MO2100XX** (Zone 1 & Zone 2)

2100 Litre Round Corrugated – 460 gallons

Dimensions:	
Diameter:	1200mm
Inlet Height:	2000mm
Total Height:	2000mm
Weight (approx.):	60kg

Tank is supplied standard with:	
1 x 300mm inlet strainer	
1 x 90mm overflow cap	
1 x 25mm (1") flush spinweld	
1 x 25mm (1") hex nipple BSP	
1 x 25mm (1") brass gate valve	


Standard fit out details:	
Inlet:	Centre – 300mm inlet strainer (no other location)
Overflow:	@ 6 o'clock – 90mm overflow (moulded into tank)
Outlet:	@ 12 o'clock – 25mm spinweld, hex nipple with 25mm brass gate valve

- When no fit out is nominated standard fit out will be supplied
- Bucket tap not included with tank
- No centre pole

Other fit out options:

- Inlet is always in the centre and overflow at 6 o'clock
- The outlet can be placed at any position on the tank
- Made in any standard COLORBOND® roofing colours

STANDARD FITOUT



*Dimensions of our tanks can vary slightly due to shrinkage variations. All dimensions are approximate

Nylex Tanks is managed and certified to the ISO9001:2008 international Quality Management Systems standard and our tanks are manufactured in Australia using UV stabilised Polyethylene complying with AS/NZS 4020 and AS/NZS 2070.

