

Code: **NT2250XX** (Zone 1)

2250 Litre Round – 500 gallons

Dimensions:	
Width/Diameter:	1400mm
Inlet Height:	1730mm
Total Height:	1800mm
Weight (approx.)	60kg

Tank is supplied standard with:	
1 x 400mm inlet strainer	
1 x 90mm overflow	
1 x 90mm overflow cap	
1 x 25mm flush spinweld	
1 x 25mm hex nipple	
1 x 25mm brass gate valve	

Standard fit out details:	
Inlet:	@ 12 o'clock – 400mm inlet strainer
Overflow:	@ 6 o'clock – 90mm overflow
Outlet:	@ 12 o'clock – 25mm spinweld, hex nipple with 25mm brass gate valve


- When no fit out is nominated standard fit out will be supplied
- Bucket tap not included with tank

Other fit out options:

- Inlet is always at 12 o'clock
- The overflow and outlet can be placed at any position on the tank
- Made in any standard COLORBOND® roofing colours



STANDARD FITOUT



*Dimensions of our tanks can vary slightly due to shrinkage variations. All dimensions are approximate

Nylex Tanks is managed and certified to the ISO9001:2008 international Quality Management Systems standard and our tanks are manufactured and certified to Australian Polyethylene tank standard AS/NZS4766:2006.

All Nylex tanks are manufactured in Australia using UV stabilised Polyethylene complying with AS/NZS 4020 and AS/NZS 2070.

