

Code: **MO2500XX** (Zone 1)

2500 Litre SUPA Slimline – 550 gallons

Dimensions:	
Length:	2600mm
Diameter/Width:	620mm
Inlet Height:	2200mm
Total Height:	2200mm
Weight (approx.):	150kg

Tank is supplied standard with:	
1 x 300mm inlet strainer	
1 x 90mm overflow cap	
1 x 25mm (1") flush spinweld	
1 x 25mm (1") hex nipple BSP	
1 x 25mm (1") brass gate valve	

Standard fit out details:	
Inlet:	@ 3 o'clock (right side of tank) – 300mm inlet strainer
Overflow:	@ 9 o'clock (left side of tank) – 90mm overflow (no other location)
Outlet:	@ 3 o'clock (right side of tank) – 25mm spinweld, hex nipple with 25mm brass gate valve

Other fit out options:	
Inlet:	@ 9 o'clock (left side of tank) – extra costs apply, other inlet needs to be capped
Overflow:	@ 9 o'clock (left side of tank) – moulded into tank (no other location)
Outlet:	@ 9 o'clock (left side of tank) – 25mm spinweld, hex nipple with 25mm brass gate valve



- When no fit out is nominated standard fit out will be supplied
- Bucket tap not included with tank
- Made in any standard COLORBOND® roofing colours

*Dimensions of our tanks can vary slightly due to shrinkage variations. All dimensions are approximate

Nylex Tanks is managed and certified to the ISO9001:2015 International Quality Management Systems standard.

All Nylex tanks are manufactured in Australia to the Australian Polyethylene tank standard using UV stabilised Polyethylene complying with AS/NZS 4020 and AS/NZS 2070.

